



iFace 302

➔ Multi-biometric Identification Time Attendance and Access Control System

CPU: Multi-Bio CPU 800 MHz
Memory: 256M Flash, 64M SDRAM
Camera: High Resolution Infrared Camera
Display: 4.3" TFT touch screen
Algorithm Version: Face 7.0, Finger 10.0 version
FAR: $\leq 0.0001\%$ | FRR: $\leq 1\%$
Fingerprint Sensor: 500 DPI Optical Sensor
Fingerprint Capacity: 2000
Face Capacity: 1200 (1:N), 3000 (1:1)
Transaction Capacity: 1,00,000
Inbuilt Proximity Card Reader
Communication: TCP/IP, RS232/485, Two USB-host
Access Control: Supports EM Lock, Exit button
Wiegand Signal: Output
Power Supply: 12V, 3A
Verification Speed: ≤ 2 sec
Operating Temperature: $0^{\circ}\text{C} - 45^{\circ}\text{C}$
Operating Humidity: 20% - 80%
Dimension (LxWxT): 193.6 x 146.8 x 111 mm

Standard Functions:

- ▶ Self Service Query
- ▶ 9 digit user ID
- ▶ Automatic Status Switch
- ▶ Workcode
- ▶ T9 Input

Optional Features:

- ▶ Mifare Card
- ▶ Wi-Fi / Web-server / GPRS
- ▶ Short Message